

### 13A Fused Connection Units

#### Product Features:

Our full range of 13A fused connection units combine safety and durability while still retaining that stylish finish backed by a 25 year warranty.

- Double pole switching on switched units
- Available with neon, flex outlet, switched or unswitched
- Current & voltage ratings printed on back for clarity
- Rockers available in white, black and metal finishes
- Designed & Manufactured in Great Britain

#### Plate Style:

Available in Signature (square edge), Reflect (round edge), Flatplate, Lyric (screwless low profile), Edwardian & Georgian, Aspire (white moulded) and Traditional (white moulded).

#### Technical Data

<b>Compliance Standard</b>	BS 1363	<b>Ambient operating temperature</b>	-5 to +40°C (24 hour average not exceeding 25°C)
<b>Rated voltage</b>	250V	<b>Maximum installation Altitude</b>	2000 metres
<b>Rated current</b>	13A	<b>IP Rating</b>	IP2XD
<b>Rated frequency</b>	50Hz	<b>Fixing screws</b>	2 x 3.5mm (M3.5)
<b>Switch contact gap</b>	3mm		
<b>Operational testing</b>	> 30,000		
<b>Terminal capacity</b>	2 x 6mm <sup>2</sup> 3 x 4mm <sup>2</sup>		

Plate Style	Dimensions (mm)					Plate Material	Min Depth Wall Box
	W1	W2	H	D1	D2		
Aspire	87		87	9.5	16.5	Plastic (Thermoset)	25
Traditional	87		87	12.5	12.5	Plastic (Thermoset)	25
Georgian	88.5		88.5	10	16	Cast Brass	25
Edwardian	88.5		88.5	8.5	17.5	Cast Brass	25
Flatplate	86		86	1.5	24.5	Brass , Stainless Steel	35
Reflect	87		87	9	17	Brass , Stainless Steel	25
Signature	88.5		88.5	7.5	18.5	Brass , Stainless Steel	25
Lyric	86		86	5	21	Brass , Stainless Steel , Copper	35

\* For Signature Double Plate H = 86.5

