

13A Socket outlets

Product Features:

Our full range of 13A socket outlets combines safety and durability while still retaining that stylish finish backed by a 25 year warranty.

- Available with neon's
- Dual and clean earth versions available
- All switched versions are double pole
- Current & voltage ratings printed on back for clarity
- Rockers available in white, black and metal finishes
- Designed & Manufactured in Great Britain

Plate Style:

Available in Signature (square edge), Reflect (round edge), Flatplate, Lyric (screwless low profile), Edwardian & Georgian, Aspire (white moulded) and Traditional (white moulded).



Technical Data

Compliance Standard	BS 1363	Ambient operating temperature	-5 to +40°C (24 hour average not exceeding 25°C)
Rated voltage	250V a.c	Maximum installation Altitude	2000 metres
Rated current	13 amp	IP Rating	IP3XD
Rated frequency	50Hz	Fixing screws	2 x 3.5mm (M3.5)
Switch contact gap	3mm		
Operational testing	>30'000		
Terminal capacity	3 x 4mm ² 2 x 6mm ²		

Plate Style	Dimensions (mm)					Plate Material	Min Depth Wall Box
	W1	W2	H	D1	D2		
Aspire	85	145	85	9.5	16.5	Plastic (Thermoset)	25mm
Traditional	85	145	85	12.5	12.5	Plastic (Thermoset)	25mm
Georgian	87	146	87	10	16	Cast Brass	25mm
Edwardian	87	146	87	8.5	17.5	Cast Brass	25mm
Flatplate	86	145	86	1.5	24.5	Brass , Stainless Steel	35mm
Reflect	87	147	87	9	15	Brass , Stainless Steel	25mm
Signature	88.5	146	88.5	7.5	18	Brass , Stainless Steel	25mm
Lyric	86	145	86	5	22	Brass , Stainless Steel , Copper	35mm

* For Signature Double Plate H = 86.5

