

### 20A and 32A DP Switches

#### Product Features:

Our full range of 20 and 32A DP switches combine safety and durability while still retaining that stylish finish backed by a 25 year warranty.

- Double pole switching
- Available with neon and flex outlet
- Can be supplied with legends
- Current & voltage ratings printed on back for clarity
- Rockers available in white, black, red and metal finishes
- Designed & Manufactured in Great Britain

#### Plate Style:

Available in Signature (square edge), Reflect (round edge), Flatplate, Lyric (screwless low profile), Edwardian & Georgian, Aspire (white moulded), Traditional (white moulded) and Metal clad.



#### Technical Data

<b>Compliance Standard</b>	BS EN 60669	<b>Ambient operating temperature</b>	-5 to +40°C (24 hour average not exceeding 25°C)
<b>Rated voltage</b>	250V	<b>Maximum installation Altitude</b>	2000 metres
<b>Rated current</b>	20A and 32A	<b>IP Rating</b>	IP4X
<b>Rated frequency</b>	50Hz	<b>Fixing screws</b>	2 x 3.5mm (M3.5)
<b>Switch contact gap</b>	3mm		
<b>Operational testing</b>	> 20,000		
<b>Terminal capacity</b>	up to 10mm <sup>2</sup>		

Plate Style	Dimensions (mm)					Plate Material	Min Depth Wall Box
	W1	W2	H	D1	D2		
Aspire	87		87	9.5	13.5	Plastic (Thermoset)	25
Traditional	87		87	12.5	9.5	Plastic (Thermoset)	25
Georgian	87		87	10	13	Cast Brass	25
Edwardian	87		87	8.5	14.5	Cast Brass	25
Flatplate	86		86	1.5	21.5	Brass , Stainless Steel	35
Reflect	87		87	9	14	Brass , Stainless Steel	25
Signature	87		87	7.5	15.5	Brass , Stainless Steel	25
Lyric	86		86	5	18	Brass , Stainless Steel , Copper	35
Metal Clad	82		82	4	21	Powder Coated Steel	Complete 45

\* For Signature Double Plate H = 86.5

