

2A Socket outlets

Product Features:

Our full range of 2A socket outlets combines safety and durability while still retaining that stylish finish backed by a 25 year warranty.

- Dual and clean earth versions available
- All switched versions are double pole
- Current & voltage ratings printed on back for clarity
- Decorative inserts available in white and black
- Designed & Manufactured in Great Britain

Plate Style:

Available in Signature (square edge), Reflect (round edge), Flatplate, Lyric (screwless low profile), Edwardian & Georgian, Aspire (white moulded) and Traditional (white moulded).

Technical Data

Compliance Standard	BS 546	Ambient operating temperature	-5 to +40°C (24 hour average not exceeding 25°C)
Rated voltage	250V a.c	Maximum installation Altitude	2000 metres
Rated current	2 amp	IP Rating	IP3XD
Rated frequency	50Hz	Fixing screws	2 x 3.5mm (M3.5)
Switch contact gap	n/a		
Operational testing	>30'000		
Terminal capacity	2 x 2.5mm ²		

Plate Style	Dimensions (mm)					Plate Material	Min Depth Wall Box
	W1	W2	H	D1	D2		
Aspire	85		85	9.5	14.2	Plastic (Thermoset)	25mm
Traditional	85		85	10	14.5	Plastic (Thermoset)	25mm
Georgian	87		87	10	16	Cast Brass	25mm
Edwardian	87		87	8.5	17.5	Cast Brass	25mm
Flatplate	86		86	1.5	24.5	Brass , Stainless Steel	35mm
Reflect	87		87	9	15	Brass , Stainless Steel	25mm
Signature	88.5		88.5	7.5	18	Brass , Stainless Steel	25mm
Lyric	86		86	5	22	Brass , Stainless Steel , Copper	35mm

* For Signature Double Plate H = 86.5

