

45A Switches

Product Features:

Our full range of 45A switches combine safety and durability while still retaining that stylish finish backed by a 25 year warranty.

- Double pole switching
- Available with neon's
- Current & voltage ratings printed on back for clarity
- Rockers available in white and red in moulded range decorative range rocker is also available in black
- Designed & Manufactured in Great Britain

Plate Style:

Available in Signature (square edge), Reflect (round edge), Flatplate, Lyric (screwless low profile), Edwardian & Georgian, Aspire (white moulded) and Traditional (white moulded).



Technical Data

Compliance Standard	BS EN 60669	Ambient operating temperature	-5 to +40°C (24 hour average not exceeding 25°C)
Rated voltage	250V	Maximum installation Altitude	2000 metres
Rated current	45A	IP Rating	IP4X
Rated frequency	50Hz	Fixing screws	2 x 3.5mm (M3.5)
Switch contact gap	3mm		
Operational testing	>10,000		
Terminal capacity	up to 16mm ²		

Plate Style	Dimensions (mm)					Plate Material	Min Depth Wall Box
	W1	H1	H	D1	D2		
Aspire	87	147	87	9.5	24.5	Plastic (Thermoset)	47
Traditional	87	147	87	12.5	21.5	Plastic (Thermoset)	47
Georgian	88.5	146	88.5	10	24	Cast Brass	47
Edwardian	88.5	146	88.5	8.5	25.5	Cast Brass	47
Flatplate	86	146	86	1.5	33.5	Brass , Stainless Steel	47
Reflect	87	147	87	9	25	Brass , Stainless Steel	47
Signature	88.5	146	88.5	7.5	26.5	Brass , Stainless Steel	47
Lyric	86	146	86	5	29	Brass , Stainless Steel , Copper	47

* For Signature Double Plate H = 86.5

