

### TV/FM and Satellite Socket Outlets

#### Product Features:

Our wide range of TV/FM and Satellite outlets combine safety and durability while still retaining that stylish finish backed by a 25 year warranty.

- Isolated outlets (dedicated cable for each signal)
- Fully rated to 10 Amps for fluorescent & inductive loads
- Intermediate & 2 way switches can be wired as 1 or 2 way
- Current & voltage ratings printed on back for clarity
- Rockers available in white, black and metal finishes
- Designed & Manufactured in Great Britain

#### Plate Style:

Available in Signature (square edge), Reflect (round edge), Flatplate, Lyric (screwless low profile), Edwardian & Georgian, Aspire (white moulded) and Traditional (white moulded).



#### Technical Data

Compliance Standard	Ambient operating temperature	-5 to +40°C (24 hour average not exceeding 25°C)
Rated voltage	Maximum installation Altitude	2000 metres
Rated current	IP Rating	
Rated frequency	Fixing screws	2 x 3.5mm (M3.5)
Switch contact gap		
Operational testing		
Terminal capacity		

Plate Style	Dimensions (mm)						Plate Material	Min Depth Wall Box
	W1	W2	H	D1	D2			
					Single/double	Triplexer		
Aspire	85		85	9.5	14	22.2	Plastic (Thermosets)	25
Traditional	85		85	9.5	14	22.2	Plastic (Thermosets)	25
Georgian	85.5		85.5	10	16.5	21.4	Cast Brass	25
Edwardian	85.5		85.5	8	18.5	23.4	Cast Brass	25
Flatplate	85		85	1.6	24	29.8	Brass , Stainless Steel	25
Reflect	87		87	9	17.3	22.4	Brass , Stainless Steel	25
Signature	88		88	7.7	18.5	23.7	Brass , Stainless Steel	25
Lyric	86		86	5.5	21	25.9	Brass , Stainless Steel , Copper	25

\* For Signature Double Plate H = 86.5