

45A Cooker Control Unit

Product Features:

Our full range of cooker control units combine safety and durability while still retaining that stylish finish backed by a 25 year warranty.

- Double pole switching
- Available with neon's for both socket and switch
- Current & voltage ratings printed on back for clarity
- Rockers available in white and red in the moulded range decorative range black, white and red for large rocker and white, black and metal for socket rocker
- Designed & Manufactured in Great Britain

Plate Style:

Available in Signature (square edge), Reflect (round edge), Flatplate, Lyric (screwless low profile), Edwardian & Georgian, Aspire (white moulded) and Traditional (white moulded).

Technical Data

Compliance Standard	BS 4177	Ambient operating temperature	-5 to +40°C (24 hour average not exceeding 25°C)
Rated voltage	250V	Maximum installation Altitude	2000 metres
Rated current	45A	IP Rating	IP3XD
Rated frequency	50Hz	Fixing screws	2 x 3.5mm (M3.5)
Switch contact gap	3mm		
Operational testing	>10,000		
Terminal capacity	up to 16mm ²		

Plate Style	Dimensions (mm)					Plate Material	Min Depth Wall Box
	W1	W2	H	D1	D2		
Aspire	147		87	9.5	24.5	Plastic (Thermoset)	47
Traditional	147		87	12.5	21.5	Plastic (Thermoset)	47
Georgian	147		87	10	24	Cast Brass	47
Edwardian	147		87	8.5	25.5	Cast Brass	47
Flatplate	146		86	1.5	33.5	Brass , Stainless Steel	47
Reflect	147		87	9	25	Brass , Stainless Steel	47
Signature	146		88.5	7.5	26.5	Brass , Stainless Steel	47
Lyric	146		86	5	29	Brass , Stainless Steel , Copper	47

* For Signature Double Plate H = 86.5

