

Fan Isolator

Product Features:

Fan Isolators combine safety and durability while still retaining that stylish finish backed by a 25 year warranty.

- Fully rated to 10 Amps for fluorescent & inductive loads
- Current & voltage ratings printed on back for clarity
- Rockers available in white and black finishes
- Designed & Manufactured in Great Britain
- Plate printed with isolator and fan symbol

Plate Style:

Available in Signature (square edge), Reflect (round edge), Flatplate, Lyric (screwless low profile), Edwardian & Georgian, Aspire (white moulded) and Traditional (white moulded).



Technical Data

Compliance Standard	BS EN 60669	Ambient operating temperature	-5 to +40°C (24 hour average not exceeding 25°C)
Rated voltage	250V AC	Maximum installation Altitude	2000 metres
Rated current	10AX	IP Rating	IP4X
Rated frequency	50 Hz	Fixing screws	2 x 3.5mm (M3.5)
Switch contact gap	3mm minimum		
Operational testing at 10A	> 40,000 ops		
Terminal capacity	4 x 1.0mm ² 3 x 1.5mm ² 2 x 2.5mm ²		

Plate Style	Dimensions (mm)					Plate Material	Min Depth Wall Box
	W1	W2	H	D1	D2		
Aspire	85	145	85	9.5	10.7	Plastic (Thermosets)	16
Traditional	85	145	85	9.5	10.7	Plastic (Thermosets)	16
Georgian	85.5	146	85.5	10	9.7	Cast Brass	16
Edwardian	85.5	146	85.5	8	11.7	Cast Brass	16
Flatplate	85	145	85	1.6	18.5	Brass , Stainless Steel	25
Reflect	87	147	87	9	10.5	Brass , Stainless Steel	16
Signature	88	146	88*	7.7	11.7	Brass , Stainless Steel	16
Lyric	86	146	86	5.5	14	Brass , Stainless Steel , Copper	25

* For Signature Double Plate H = 86.5

