



3467WS

3469RS

Key switch connection units

Product Features:

Our full range of key switch connection units combine safety and durability while still retaining that stylish finish backed by a 25 year warranty.

- Available with neon and flex outlet or both
- Red, white and metal finishes
- Flush and surface mounting
- Supplied with double ended key, one end controls switch, the other withdraws the fuse holder
- Labels are provided for identification: "DO NOT SWITCH OFF", "BURGLAR ALARM", "FIRE ALARM", "NURSE CALL PANEL"
- Designed & Manufactured in Great Britain

Plate Style:

Available in:

Metalclad (red or metal colour).

Reflect (red or white colour).

Technical Data

Compliance Standard	BS 1363	Ambient operating temperature	-5 to +40°C (24 hour average not exceeding 25°C)
Rated voltage	250 volts	Maximum installation Altitude	2000 metres
Rated current	13 amp	IP Rating	IP 2X
Rated frequency	50Hz	Fixing screws	2 x 3.5mm (M3.5)
Switch contact gap	3mm Min	Flex outlet	1 x 2.5mm ² 3 core flexible cord
Operational testing	>15000 cycles	Fuse fitted	1 x 13 amp BS 1362
Terminal capacity	3 x 4mm ² 2 x 6mm ²		

Dimensions:

Plate	Fixing centres	Dimensions	Min wall box depth
Metalclad	60.3	81.5 x 81.5 x 44	
Reflect	60.3	87 x 87	25mm