

Shaver socket outlet

Product Features:

Our full range of shaver sockets combine safety and durability while still retaining that stylish finish backed by a 25 year warranty.

- Double gang socket (1 x 110V and 1 x 240V)
- Fully isolated transformer for increased safety
- Fitted with a temperature & current sensing thermister to protect against overload and misuse
- Safety auto switching shutters to prevent more than one plug being inserted at one time
- Suitable for bathrooms when installed in accordance with BS 7671 IEE wiring regulations
- Designed & Manufactured in Great Britain



Plate Style:

Available in Signature (square edge), Reflect (round edge), Flatplate, Lyric (screwless low profile), Edwardian & Georgian, Aspire (white moulded) and Traditional (white moulded).

Technical Data

Compliance Standard	BS EN 61558-1 BS EN 61558-2-5 BS EN 60742 / BS 3535-1	Ambient operating temperature	-5 to +40°C (24 hour average not exceeding 25°C)
Rated voltage, Input	220V - 240V	Maximum installation Altitude	2000 metres
Rated voltage, output	115V & 240V	IP Rating	IP2XD
Rated frequency	50Hz	Fixing screws	2 x 3.5mm (M3.5)
Transformer power	20VA		
Operational testing			
Terminal capacity			

Plate Style	Dimensions (mm)					Plate Material	Min Depth Wall Box
	W	H	D1	D2			
Aspire	85	145	10	39	Plastic (Thermoset)	47mm	
Traditional	85	145	13	35	Plastic (Thermoset)	47mm	
Georgian	87	147	10.5	38	Cast Brass	47mm	
Edwardian	87	146	8.5	40	Cast Brass	47mm	
Flatplate	85	145	1.5	47	Brass , Stainless Steel	47mm	
Reflect	87	147	8.5	39	Brass , Stainless Steel	47mm	
Signature	86	146	7.5	41	Brass , Stainless Steel	47mm	
Lyric	86	146	5.5	41	Brass , Stainless Steel , Copper	47mm	

* For Signature Double Plate H = 86.5

