# Technical Specification

LYR3722PSWM - 2 Gang 2 Way 10AX



## General

**Box quantity:** 1
**GTIN-13 / EAN:** 5056199052448
**Total gross weight (g) includes packing:** 154.00
**Total net weight (g) excluding packaging:** 149.00
**Individual unit weight (g):** 149.00
**Width mm:** 85.00
**Height mm:** 85.00
**Depth mm:** 20.00
**Size/Dimensions (mm):** 85X85X20
**Surf area M^2:** 0.021

## Technical

**ABC indicator:** A
**Insert colour:** white
**Face plate finish:** polished steel
**Rocker finish:** polished steel
**Number of rockers:** 2
**Associated standards:** BS EN 60669-1
**Rated voltage:** 220-250V
**Rated current:** 10AX
**Frequency:** 50-60Hz
**Wiring system:** 1 pole
**Min. switch contact gap:** 3mm
**Ambient operating temperature:**
-5 to 40°C (24hour average not exceeding 25°C)
**Degree of protection:** IP2X
**Terminal capacity:** 3 x 1.0mm 3 x 1.5mm 1 x 2.5mm
**Face plate material:** high grade stainless steel
**Minimum wall box depth:** 25
**Nature of supply:** AC
**Fixing screws:** 2 x M3.5