CONTACTUM

Technical Specification

CLA4900M - 2 Gang 13A Latching Socket DP



General

 $\ \, \textbf{Box quantity:} \ 1$

GTIN-13 / EAN: 5056199015153

Total gross weight (g) includes packing: 561.00 Total net weight (g) excluding packaging: 503.00

Individual unit weight (g): 503.00

Width mm: 140.00 Height mm: 80.00 Depth mm: 45.00

Size/Dimensions (mm): 140X80X45

Surf area M^2: 0.042

Technical

ABC indicator: A Insert colour: white

Fault current protection (RCD): 30mA

Face plate finish: metal Rocker finish: white moulded Number of rockers: 2 Number of outlets: 2

Number of socket outlets switchable: 2

Associated standards:

BS7288: 2016 & BS 1363-2: 2016 +A1: 2018

Rated voltage: 220-250V Rated current: 13A Frequency: 50-60Hz Wiring system: 2 pole

Min. switch contact gap: 3mm

Ambient operating temperature:

-5 to 40°C (24hour average not exceeding 25°C)

Degree of protection: IP2X

Terminal capacity: 3 x 2.5mm 3 x 4.0mm 2 x 6.0mm

Face plate material: steel Nature of supply: AC Rated fault current: 30mA Fixing screws: 2 x M3.5 Mounting method: surface

RCD Type: Type A

