CONTACTUM

Technical Specification

ALF4900WHW - 13A 2G DP Switch Skt RCD 30mA (Latching)



General

Box quantity: 1

Total gross weight (g) includes packing: 287.00 Total net weight (g) excluding packaging: 213.00

Individual unit weight (g): 213.00

Width mm: 147.00 Height mm: 95.00 Depth mm: 40.00

Size/Dimensions (mm): 147X95X40

Surf area M^2: 0.047

Technical

ABC indicator: A
Colour: White
Insert colour: white
Face plate finish: moulded
Rocker finish: white moulded

Number of rockers: 2 Number of outlets: 2

Number of socket outlets switchable: 2

Associated standards:

BS7288: 2016 & BS 1363-2: 2016 +A1: 2018

Rated voltage: 220-250V Rated current: 13A Frequency: 50-60Hz Wiring system: 2 pole

Min. switch contact gap: 3mm

Ambient operating temperature:

-5 to 40°C (24hour average not exceeding 25°C)

Degree of protection: IP2X

Terminal capacity: 3 x 2.5mm 3 x 4.0mm 2 x 6.0mm

Face plate material: polycarbonate Minimum wall box depth: 35 Nature of supply: AC

Rated fault current: 30mA Fixing screws: 2 x M3.5

