CONTACTUM



Technical Specification

CON6356BSB - 2 Gang 13A DP Switched Socket + USB 5v/4800mA BS Black Insert Plastic Rocker



General

Box quantity: 1

Total gross weight (g) includes packing: 274.00 Total net weight (g) excluding packaging: 264.00

Individual unit weight (g): 264.00

Width mm: 145.00 Height mm: 85.00 Depth mm: 30.00

Size/Dimensions (mm): 145X85X30

Surf area M^2: 0.038

Technical

ABC indicator: A **Insert colour:** black

Face plate finish: brushed steel
Rocker finish: black moulded
Number of rockers: 2
Number of outlets: 2

Number of socket outlets switchable: 2
Associated standards: BS 1363-2 2016+A1:2018

Rated voltage: 220-250V

Rated current: 13A Frequency: 50-60Hz Wiring system: 2 pole

Min. switch contact gap: 3mm

Ambient operating temperature:

-5 to 40°C (24hour average not exceeding 25°C)

Degree of protection: IP2X

With built-in USB power supply: yes

Terminal capacity: 3 x 2.5mm 2 x 4.0mm 2 x 6.0mm **Face plate material:** high grade stainless steel

Surface protection: lacquered Minimum wall box depth: 35 Nature of supply: AC

Fixing screws: 2 x M3.5

