
CONTACTUM



Technical Specification

LYR6346BSW - 1 Gang 13A DP Switched Socket + USB 5v/2100mA BS White Insert Plastic Rocker





AWAITING IMAGE

General

 $\ \, \textbf{Box quantity:} \ 1$

Total gross weight (g) includes packing: 189.00 Total net weight (g) excluding packaging: 184.00

Individual unit weight (g): 184.00

Width mm: 85.00 Height mm: 85.00 Depth mm: 30.00

Size/Dimensions (mm): 85X85X30

Surf area M^2: 0.025

Technical

ABC indicator: A
Insert colour: white

Face plate finish: brushed steel Rocker finish: white moulded Number of rockers: 1 Number of outlets: 1

Number of socket outlets switchable: 1 Associated standards: BS 1363-2 2016+A1:2018

Rated voltage: 220-250V Rated current: 13A Frequency: 50-60Hz Wiring system: 2 pole

Min. switch contact gap: 3mm

Ambient operating temperature:

-5 to 40°C (24hour average not exceeding 25°C)

Degree of protection: IP2X

With built-in USB power supply: yes

Terminal capacity: 3 x 2.5mm 2 x 4.0mm 2 x 6.0mm **Face plate material:** high grade stainless steel

Surface protection: lacquered Minimum wall box depth: 35 Nature of supply: AC

Fixing screws: 2 x M3.5

