CONTACTUM



Technical Specification

LYR6346PBW - 1 Gang 13A DP Switched Socket + USB 5v/2100mA PB White Insert Plastic Rocker





AWAITING IMAGE

General

Box quantity: 1

Total gross weight (g) includes packing: 194.00 Total net weight (g) excluding packaging: 189.00

Individual unit weight (g): 189.00

Width mm: 85.00 Height mm: 85.00 Depth mm: 30.00

Size/Dimensions (mm): 85X85X30

Surf area M^2: 0.025

Technical

ABC indicator: B **Insert colour:** white

Face plate finish: polished brass Rocker finish: white moulded Number of rockers: 1

Number of outlets: 1Number of socket outlets switchable: 1

Associated standards: BS 1363-2 2016+A1:2018

Rated voltage: 220-250V Rated current: 13A Frequency: 50-60Hz Wiring system: 2 pole

Min. switch contact gap: 3mm

Ambient operating temperature:

-5 to 40°C (24hour average not exceeding 25°C) **Degree of protection:** IP2X

With built-in USB power supply: yes

Terminal capacity: 3 x 2.5mm 2 x 4.0mm 2 x 6.0mm **Face plate material:** high grade electro plated stainless steel

Surface protection: lacquered Minimum wall box depth: 35 Nature of supply: AC

Fixing screws: 2 x M3.5

