



Technical Specification

DD101SPMS-P01 - 10 Way Pop 100A Sw + SPD + 6 RCBO's & 4 Blanks



General

Box quantity: 1
Colour: White
Total gross weight (g) includes packing: 5600.00
Total net weight (g) excluding packaging: 5260.00
Individual unit weight (g): 5260.00
Width mm: 330.00
Height mm: 260.00
Depth mm: 130.00
Size/Dimensions (mm): 330X260X130
Surf area M²: 0.325

Technical

ABC indicator: B
Security features: optional security lock available
Associated standards: BS EN 61439-3
Rated voltage: 220-250V
Rated current: 100A
Frequency: 50-60Hz
Wiring system: 2 pole
Ambient operating temperature:
-5 to 40°C (24hour average not exceeding 25°C)
Degree of protection: IP4X
Width in number of modular spacings: 14
Nature of supply: AC
DIN-rail: yes
Extension possible: yes
Type of cover: steel
Type of door: steel
Material housing: steel
Plate thickness cabinet: 1.2
Plate thickness door/cover: 1.2
Mounting method: surface
With mounting plate: RCEB-TE-14MOD
Number of outgoing ways: 10
Surge Device Spec:
Uc - 275V
In - 10kA
Imax - 20kA
Up - ≤1.2kV
Green (ok) Red (replace) status indicator