## **CONTACTUM**



## **Technical Specification**

LYR3457PBW - 45A DP Sw RR+13A Neon PB White Insert Plastic Rocker



## General

Box quantity: 1

Total gross weight (g) includes packing: 312.00 Total net weight (g) excluding packaging: 305.00

Individual unit weight (g): 305.00

Width mm: 145.00 Height mm: 85.00 Depth mm: 35.00

Size/Dimensions (mm): 145X85X35

Surf area M^2: 0.041

## **Technical**

**ABC indicator:** B **Insert colour:** white

Face plate finish: polished brass Rocker finish: white moulded With indicator lamp: yes Number of rockers: 2 Number of outlets: 1

Number of socket outlets switchable:  $\boldsymbol{1}$ 

Associated standards: BS 4177 Rated voltage: 220-250V Rated current: 45A Frequency: 50-60Hz Wiring system: 2 pole

Min. switch contact gap: 3mm

Ambient operating temperature:

-5 to 40°C (24hour average not exceeding 25°C)

Degree of protection: IP2X

Terminal capacity: 2 x 4mm 1 x 6mm 1 x 10mm

Face plate material: high grade electro plated stainless steel

Surface protection: lacquered Minimum wall box depth: 47

Nature of supply: AC Fixing screws: 2 x M3.5

